



- Designed by Keyscan specifically for use with Keyscan Access Controllers and Keyscan's Access Control Management Software.
- MC33H is supplied with housing and plug-in transformer for simplified installation at a computer running Keyscan's System VII Software.
- MC9600 (Panel Mount) is powered from the ACU's 12 VDC battery backed up power supply for faster installations and reliable operation even in power outages.
- Pre-loaded with standard setup parameters to ensure trouble free connection the first time.
- Additional modem and ACU settings are updated by Keyscan's Access Control Management Software.
- Fast, easy, trouble-free installation.


MC9600 & MC33H

KEYSCAN DIAL-UP MODEM

FEATURES AND BENEFITS

- Fast easy installation either at the host computer or inside the Keyscan Access Control Unit (ACU).
- Factory default settings virtually guarantee establishing successful communications the first time.
- Keyscan's Access Control Management Software updates all the ACU's with the information they need to operate efficiently whether direct connect or via modem.
- Automatically adjusts to the appropriate speed for local line conditions.
- Simplifies installations since the modem can be installed at any convenient ACU location.
- Operates with both pulse and tone analogue telephone systems.
- Expands system capacity without affecting direct connected devices.
- Modem can be used to link a remote site to the host computer regardless of whether it is across the street or across the country.
- Can be used as a fax modem on the access control management computer if required.
- Set up strings defaulted in Keyscan's Access Control Management Software.

APPLICATIONS



SPECIFICATIONS

System Requirements:

External power supply:

Input power: MC33H: 12 VDC \pm 5% (300 mA) via 2.1 mm adapter plug (provided)
MC9600: direct wired from external 12 VDC 1A power supply

Certifications:

FCC Part 15, subsection J for a class B device, FCC Part 68, DOC, UL, CSA, CE.

Relative Humidity: 0 to 100%* Temperature: -35° to 65° C

* Resistant to moisture but not suitable for use underwater.

Dimensions: MC9600: 4" x 3" (101mm x 76mm)

MC33H: 4.5" x 3.25" (114mm x 83mm)

Environmental Tolerances:

Suitable for light to moderate residential, commercial and industrial applications.

Relative Humidity: 0 to 100% non-condensing

Temperature: -35° to 65° C

Certifications:

FCC Part 15, subsection J for a class B device, UL, CSA, CE

KEYSCAN INC.

901 Burns Street East, Whitby, Ontario L1N 6A6

Phone: 905.430.7226 Toll Free: 1.888.539.7226 Fax: 905.430.7275

www.keyscaan.ca

Keyscan Inc. reserves the right to alter designs and specifications without notice or obligation

Rev.: 10-2010